



RGB+2 DoubleDATA Line Pebble Lights

RGB+2-PEB

In association with



Lens: clear, frosted

Pitch: 4-, 6-, 12-inch, custom

View Angle: single-, or double-sided

Bulb Count: 5-, 10-, 25-light, custom

Wire Color: black, green, white

Ends: thru-connect, terminated

Output	
LED Type	SMD3535
LED Channels	R-G-B
Protocol	UCS5603
Greyscale	12-bit, 4096 dimming levels*
LED Quantity	2
Chipset	RGB+2 (4-wire; DoubleDATA line)
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Lights before power injection	approx. 200L
Max Distance before Power Injection	approx. 220-feet
Electrical & Safety	
Input Voltage	24 VDC
Current	0.015 Amps
Power	0.36 Watts
Wire	20 AWG, 4C, UV protected
Inline power injection	via 4-wire Power T+'s & RGB+3A-24V
Certifications	(c)UL listed, IP 65, CE
Physical	
Diameter	1.75 x 0.75 x 0.5"
Weight	approx. 0.256 oz. per bulb
Housing	polycarbonate
Mounting bracket	yes, 2-screw hole adjustable clip; or 3-foot pvc track sections
Connector Type	LLT twist-lock
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



USA HQ
Mechanicsburg, PA
(717) 763-1055

www.minleonusa.com



* 8-bit via DDP.

Specifications as of May 2021 and are subject to change.

Powered by
MESHTEK®