



RGB+Plus Line 4-LED Pebble Lights

RGBW+PEB-4L

In association with



Lens: clear, frosted

Pitch: 4-, 6-, 12-inch, custom

View Angle: double-sided

Bulb Count: 5-, 10-, 25-light, custom

Wire Color: black, green, white

Ends: thru-connect, terminated

Output	
LED Type	SMD5050
LED Channels	R-G-B-W
Greyscale	16-bit, 65,536 dimming levels*
LED Quantity	4
Chipset	RGB+
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Lights before power injection	approx. 160L
Max Distance before Power Injection	approx. 160-feet
Electrical & Safety	
Input Voltage	24 VDC
Current	0.022 Amps
Power	0.53 Watts
Wire	18 AWG, 3C, UV protected
Inline power injection	via Power T+'s & RGB+4A-24V
Certifications	(c)UL listed, IP 65, CE
Physical	
Diameter	2.0 x 0.875 x 0.5"
Weight	approx. 0.256 oz. per bulb
Housing	polycarbonate
Mounting bracket	yes, 2-screw hole adjustable clip, add-on
Connector Type	LLT twist-lock
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



USA HQ
Mechanicsburg, PA
(717) 763-1055

www.minleonusa.com



* 8-bit via DDP.

Specifications as of July 2021 and are subject to change.

